


System Configuration Size Unit:mm

Powerhead








Console














Press Duo elite

Standard Specification	ns *A:Contrast agent B:Saline
•Flow Rate	0.1~30.0mL/sec (0.1mL/sec step)
•Volume	0.1~99.9mL (Setting Unit: 0.1mL)
•Pressure Limit	50~1200psi (400~8200kpa)
·Inject Delay	0∼99.9 sec
•X-Ray Delay	0∼99.9 sec
•Rise Time	0∼9.9 sec
·Injection Pattern	A , A+B , A+B \rightarrow A+B , A+B \rightarrow A , A \rightarrow A+B
·Protocol Memory	240 protocol
·Integrated Volume display	Yes,
·Injection Results Display	Yes, (Cases 50)
•Syringe Heater	Yes, 36℃±5℃

Angio(A+B) Mode Programming Range

•Flow Rate	A-side: 0.1~30.0mL/sec (0.1mL/sec step)
	B-side: 0.1~10.0mL/sec (0.1mL/sec step)
•Volume	0.2~99.9mL (Setting Unit: 0.1mL)
•Dilution Rate	Dilution percentage: 10-90
	Dilution ration: 1:9-9:

CT Mode Programming Range

•Flow Rate	0.2~10.0mL/sec (0.1mL/sec step)
•Volume	0.2~150.0mL (Setting Unit: 0.1mL)
·Pressure Limit	50~300psi (400~2000kpa)

Angiographic Contrast Delivery System

·Emergency Stop Buttons

Electrical Specif	ications			
·Voltage AC	115/230V	•Protection C	lass	Class I
·Power Consumption	1050VA	•Protected Le	evel	Type CF
·Frequency	50/60Hz	 Activation 	Electromech	anical drive

Safety Mechanish

·Over Pressure Monitoring

Salety McCharlisins	
•Flow Rate Monitoring	Syringe Placement Monitoring
·Overvolume Monitoring	·Injection Process Monitoring

 Dilution Injections (simultaneous injections) 	
•Quick Purge (auto air vent)	

- •X-Ray System Synchronization
- ·Injection Results Display
- •Angio Mode •CT Mode (Swich Box)

·Table Rail Mount

•NEMOTO Disposable syringe 150mL

Weight

·Main Unit: 16.0 kg ·Powerhead: 11.1kg ·Console: 5.7kg



NEMOTO KYORINDO CO., LTD. 2-27-20 Hongo, Bunkyo-ku, Tokyo 113-0033, Japan

www.nemoto-do.co.jp

*Specifications and appearance of this product may change without notice.

The specifications of this pamphlet are as of April in 2017. ©Nemoto Kyorindo Co, Ltd. 2017 All rights reserved. Catalog creation date: February 14.2017. /20170214PDE-Rev.A





The Console GUI is designed to show the protocol information quickly and easily.

Vision friendly colors and sizes chosen as another safety feature of this new injector.





The GUI includes all necessary data on one screen image.

9	2016/08	V13	Total Vo	- 1	03.0=		
1	10.0	20.0	2	1000		0.0	0.0
2	10.0	20.0	2	900	5:5	0.0	0.0
3	10.0	20.0	3	900	- 50	0.0	0.0
4	10.0	20.0	-	900	- 2	0.0	-00

Injection Results screen shows injected volume in chronological



Console with touchscreen operation. Color changes based on mode of operation.



Dual Functionality Manual Knobs



Organic EL display shows syringe remaining volume.



angiographic procedures, provides advanced features to achieve the image quality and detail expected.

One control Console, various contrast dilutions

Freely, using the control Console, set Enabling control of the iodine content the flow, volume, pressure and dilution for each examination and avoiding the for the 2 syringes. Eliminate the need to injection of excessive iodine. premix or setup special syringes, improving efficiency and hygienic environment.

Contrast Dilution Control

Our unique device design enables complete control of contrast dilution rates, making angiography exams and CT like exams possible. The PRESS DUO elite enables the full

advantage of FPD technology to be

realized.

Optimizing Iodine for Patient Safety

Use only the necessary amount.

Using Newly Developed "mixing tube", Enhanced Mixing of Contrast and Saline is Possible

Our uniquely designed "mixing tube" for PRESS DUO elite, is designed to increase image detail and accuracy.

